


DO NOT SCALE. IF IN DOUBT ASK. ALL DIMENSIONS IN MILLIMETERS UNLESS STATED OTHERWISE.



Thermoliner.  
Thermally-decoupled lining  
subframe-factory fitted.

Outline of fixing rail

Handle.

Rooflight lining. Factory  
fitted, decorated by contractor.

Timber lining  
by contractor.

Structural support  
members.

Tilting fillet.

Use hardwood or treated softwood and make,  
fillet long enough to give good downward and  
outward tilt.

Structural length.

Co-Ord length.

50mm.

Silicone bedding.  
Apply a thick continuous bead  
of low modulus neutral cure  
silicone along the width of  
the cill flashing in a position  
where it will be covered by  
the cill flange of the rooflight.  
Apply the silicone just prior  
to fitting the rooflight in  
position.

Cill flashing.  
Use TRC Flashing Kit or code  
4 lead sheet to cills. In severer  
exposures clip flashing down at  
centres and consider clipping  
down rooftiles also. Make  
the flashing long enough to  
give triple lap to the tiles  
below.

Roofing felt.

the Rooflight Company  
Wychwood Busines Centre  
Milton Road  
Shipton-Under-Wychwood  
Oxon OX7 6XU

Telephone: 01993-830-613  
Fax: 01993-831-066  
Email: info@therooflightcompany.co.uk

Please note that this drawing  
does not constitute a structural  
support proposal. Sufficiency of  
structural supports to be checked  
by rooflight purchaser's structural  
consultant.

Drawing Ref/No. 12386-02

Title. CLAY TILE CILL DETAIL  
NEO-S ROOFLIGHT

Scale. N.T.S Date:28/04/09

Drawn By:PD

Checked By:TM

Revision No. B

The information contained within this drawing is Copyright  
& Design right of the Rooflight Company