

Technical Data Sheet

The Conservation Plateau Rooflight (standard sizes)

the
Rooflight
Company

Product Description

The Conservation Plateau Rooflight is the only flat rooflight designed specifically for heritage buildings.

Manufactured From

3mm mild steel with a protective polyester powder coating to BS EN ISO 12944.

The standard frame is finished in a textured semi-gloss paint finish in black RAL 9005 (other RAL colour options are available).

All Conservation Plateau Rooflights have internal linings which are pre-treated and sealed with a white coating (to a 10% gloss level).

COASTAL: Please note, for properties that reside within 5km of the coastline or large estuary, we recommend calling our Customer Services Team on 01993 833155 to discuss an appropriate alternative of stainless steel or steel treated with a hot Zinc Spray coating.

Testing



The Conservation Plateau Rooflight range is CE marked in accordance with EN14351-1:2006+A1:2010.

Part L compliant and tested for water tightness to EN 1027:2000 - met class E1050.

The Conservation Plateau Rooflight meets the requirements of BS6375-1:2009 exposure category 2000.

Pitch

Suitable for flat roof installations with a 3-20° roof pitch.



Standard Glazing

4mm SGG Planilux Toughened Outer

16mm 90% Argon Cavity

6.4mm SGG Planitherm One Laminate Inner

Whole unit u-value (U_w) of 1.4 W/m²K in accordance with EN ISO 10077-2:2012.

Other glazing specifications are available upon request, contact us for more information.

Sizes and Prices (internal structural kerb)

PL01	(W) 625mm x (L) 625mm -	£814
PL07	(W) 925mm x (L) 625mm -	£1098
PL02	(W) 925mm x (L) 925mm -	£1255
PL08	(W) 1225mm x (L) 625mm -	£1308
PL09	(W) 1225mm x (L) 925mm -	£1570
PL03	(W) 1225mm x (L) 1225mm -	£1717
PL10	(W) 1525mm x (L) 925mm -	£1728
PL11	(W) 1525mm x (L) 1225mm -	£1877
PL04	(W) 1525mm x (L) 1525mm -	£1886
PL18	(W) 2025mm x (L) 1025mm -	£1886
PL12	(W) 2025mm x (L) 1525mm -	£2699
PL22	(W) 925mm x (L) 1525mm -	£1728
PL24	(W) 1025mm x (L) 2025mm -	£1981

Prices exclude accessories, VAT and delivery. For Bespoke sizes please contact us on 01993 833108. Sizes listed are for the internal structural kerb.

All prices are correct at the time of going to press.

Opening Options

Manual hand winders

Available in brass or chrome with opening distances of either 150mm or 300mm.

Manual pole winder

And winding crank for out of reach opening. Available in brass or chrome with opening distances of 150mm or 300mm. Poles are available in varying lengths from 1m to 3m.

Motors

Motorised opening options are available for out of reach rooflights and can be controlled by a switch or remote. Contact us for more information

Fixed Shut

A fixing bracket for a fixed shut roof window. The fixing bracket is white as standard.

Please note: The PL12 can only be fixed shut or motorised due to its size.

Optional Extras

Rain sensors, temperature sensors and other accessories are available on request. Please consult with us directly for compatibility.

Flashing Kits

Flashing Kits are not available for the Conservation Plateau Rooflight.

Lead Time

The Conservation Plateau Rooflight is available within 12 - 35 working days depending on model size and specification configured. Subject to availability.

Installation

The Conservation Plateau Rooflight Installation Manual and Installation Drawings are available to download from our website.

BIM Objects can also be downloaded.

Warranty

Our steel rooflights and roof windows are guaranteed for 12 months in accordance with our Terms and Conditions.

Upon product registration with us, this guarantee can be extended as set out in our terms and conditions, provided that the appropriate products have been installed to suit their location and that these are regularly maintained, with these actions recorded in accordance with our maintenance instructions.



Visit www.therooflightcompany.co.uk
or call us today on **01993 833108** for more
information.

the
Rooflight
Company