

Opening Options for the Conservation Rooflight®

1. Manual - Within Hand Reach

The manual opening operation requires the operator to be able to reach the cill of the roof window once it is installed. You can purchase a hand winder from the options below.



Option J -
Chrome Plated hand winder 150mm £39

Option B -
Chrome Plated hand winder 300mm £44



Option A -
Brass hand winder 150mm £44

Option E - Brass hand winder 300mm £49



Option W -
Anodised aluminium wheel on Chrome Plated hand winder 150mm £55



Option Y -
Black wheel on brass hand winder 150mm £55

3. Motorised

We offer a number of different motors for the Conservation Rooflight®. Motors are installed at the cill of the roof window. You can purchase a motor and a switch from the options below.



Option Au-Max Electric Linear actuator 230v 300mm £167

KA34-350	MAX	MAC	Supermaster	Rack
24v	230	230v/24v	230v/24v	230v/24v
350mm	300mm	150mm ONLY	420/600mm	180mm

The Conservation Rooflight®

CR1		•			
CR1/3	•	•	•		
CR2/1		•			•
CR3		•	•		
CR6		•			•
CR7		•			•
CR8		•	•		
CR9	•	•	•		
CR10	•	•	•		
CR11	•	•	•		
CR13	•	•		•	
CR14		•		•	
CR14/2	•	•	•		
CR15		•		•	
CR15/2	•	•	•		



Option MAC Motor 230v, 24v 150mm only £193



Option Supermaster Motor 230v, v24v 450mm £255



Switch £37

2. Manual - Out of Hand Reach

The 'out of hand reach' can be installed if the operator cannot reach the cill of the roof window. You will need to purchase a winding pole and a winding crank from the options below.



Option L -
Chrome Plated pole winder 150mm £39

Option C -
Chrome Plated pole winder 300mm £44



Option K -
Brass pole winder 150mm £44

Option D -
Brass pole winder 300mm £49



Option T



Option F



Option G



Option I

Option F -
Aluminium 1m length pole £33

Option G -
Aluminium 1.5m length pole £39

Option H -
Aluminium 2m length pole £44

Option I -
Aluminium 1.7m-30 length pole £49

Option T -
Anodised Pole Winder 500mm £77

4. Fixed Shut

The Conservation Rooflight® can also be fixed shut. You can purchase a fixing bracket for £6. The bracket must be installed to the cill of the roof window (see image to the right).




5. The Conservation Egress / Access Rooflight

This is only available as manually operated. The hand winders are available in brass and chrome from the options below. Motors cannot be installed on to these windows as they are designed to be installed as a means of access or entry into a room.



Option Q -
Chrome Plated hand winder 300mm £60

Only for use with the Conservation Egress Rooflight®



Option Z -
Brass hand winder 300mm £65

Only for use with the Conservation Egress Rooflight®